

**CLAIMS**

1. A process for the catalytic generation of hydrogen by the self-sustaining combination of partial oxidation and steam-reforming of a hydrocarbon comprising contacting a mixture of the hydrocarbon and an oxygen-containing gas and steam with a catalyst comprising rhodium dispersed on a refractory oxide support material which comprises as cations cerium and zirconium.

2. A process according to claim 1 wherein steam is introduced into the mixture of hydrocarbon and oxygen-containing gas after the self-sustaining partial oxidation of the hydrocarbon has commenced.

3. A process according to claim 1 or 2 wherein the hydrocarbon is a straight chain hydrocarbon or a branch chain hydrocarbon.

4. A process according to claim 3 wherein the hydrocarbon contains 1 to 15 carbon atoms.

5. A process according to claim 4 wherein the hydrocarbon contains 1 to 7 carbon atoms.

6. A process according to any one of the preceding claims wherein the hydrocarbon is selected from methane, propane, butane, hexane, heptane, normal-octane, iso-octane, naphthas, liquified petroleum gas, reformulated petrol and diesel-type fuels.

7. A process according to any one of the preceding claims wherein the oxygen-containing gas is air.

8. A process according to any one of the preceding claims wherein rhodium comprises 0.1 weight per cent to 5 weight per cent of the total weight of the supported catalyst.

30

9 A process according to claim 8 wherein rhodium comprises 0.2 weight *per cent* to 2.5 weight *per cent* of the total weight of the supported catalyst.

10. A process according to any one of the preceding claims wherein the refractory oxide support material is a mixture of ceria and zirconia.

11. A process according to claim 10 wherein the weight ratio of ceria to zirconia in the catalyst support material is from 0.5 to 99.5 to 99.5 to 0.5

10 12. A process according to claim 11 wherein the weight ratio of ceria to zirconia in the catalyst support material is from 5 to 95 to 95 to 5.

13. A process according to any one of the preceding claims wherein the catalyst is pre-heated to a temperature at which self-sustaining partial oxidation of the hydrocarbon commences.

14. A process according to claim 13 wherein the catalyst is pre-heated by direct heating to a temperature at which self-sustaining partial oxidation of the hydrocarbon commences.

20 15. A process according to claim 13 wherein the catalyst is pre-heated by catalytic heating to a temperature at which self-sustaining partial oxidation of the hydrocarbon commences.

25 16. A process according to claim 15 wherein the catalyst is pre-heated by feeding to the catalyst an oxygen-containing gas and an initiating compound which is more easily oxidisable than the hydrocarbon which is to be partially oxidised.

17. A process according to claim 16 wherein the initiating compound is selected from methanol, hydrogen and dimethyl ether.

SB  
AW

ained in any c  
r-gas shift rea  
m the hydrocar

10

5030  
A11

15

Add A12

20

06987413